
U9ht this U9ht that

LED Wall Light

316 Marine Grade Stainless Steel or Solid Copper
Extremely low voltage

"Circular Quay"





Height mm	Reach mm		
а	b		
500	2000		
750	4000		



MADE IN AUSTRALIA

The **Light This Light That** 316 'Marine Grade' Stainless Steel '35 Degree' Wall lights are available in two sizes. Your Australian Made Light This Light That LED Wall light is IP68 rated which means it can be installed outdoors.

This light system contains non replaceable parts. Do not attempt to force open the light.

Indoor/ Outdoor

model	dimensions				current	current	lense
	length (A)	depth (b)	width (c)	thickness (d)	watts	mA (max)	degrees
LTW35CCS6	55mm	35mm	38mm	2mm	0.5	40	45
LTW35CCM12	70mm	35mm	50mm	2mm	1	80	45
LTW35CCL21	115mm	45mm	77mm	2.5mm	1.75	140	45

Note: 1 Amp = 1000 milliamps (mA).

Polarity sensitive.

Disclaimer: Consistent with our product development policy, improvements may be made which render the contents of this document different to that shown. While every care has been taken with the details on this specification sheet, Light This Light That Pty Ltd accepts no responsibility for any inaccuracies and reserves the right to change the specifications without incurring obligation. Light This Light That Pty Ltd reserves the right to change specifications without notice.

© Copyright 2013 Light This Light That Pty. Ltd.

Specifications:

Materials: <u>Casing:</u> 316 Marine Grade

Stainless Steel (or solid copper) 316 Stainless Steel body is

electroplated for additional protection

against "tea staining"

<u>Flange:</u> 316 Marine Grade
Stainless steel (or solid copper)

<u>Face:</u> is made from weatherproof

premium quality acrylic

Power Source:

Low Voltage 12 V DC input

(regulated)

Weatherproof

Rating: IP 68

Pre wired: Rear entry 900mm (length)

weatherproof cable (20 gauge)

Warranty: 3 years for electrics

10 years for 316 Stainless Steel and

Solid Copper casing

Cabling: Light This Light That Weatherproof

harness (18 gauge) with screw in plugs, or similar (see Light This Light That Accessories Catalogue)

LED type: State of art: **NICHI** :5mm

Lights are polarity sensitive

LED Colours: Cool White Typical 5300 K

Warm White Typical 3000 K

N30415 Complies with standards
AS/ NZS CISPR 15: 2006

Features:

Australian Owned

Australian Made

Extremely low energy consumption

12 volt low voltage Up to 60,000 hours life No globes to change Directional light efficiency

Ambient light

Solid state technology

No fragile glass environment

Non corrosive body

Ideal for coastal environments

No Ultraviolet radiation No Infrared radiation No UV to attract insects

Cool to touch

Doesn't burn plants

No Mercury Portable

Easy installation, easy to move

Choice of sizes

IP 68 - highest water proof rating

No condensation issues

Electrics protected from syphoning damage

Australian Owned & Australian Made



Distributor